



22SV SERIES
DIMENSIONS AND WEIGHTS AT 50 Hz, 2 POLES


PUMP TYPE	DIMENSIONS (mm)												WEIGHT kg		
	MOTOR	kW	SIZE	L1	L2		L3	L4	L5	M	D1		PUMP	ELECTRIC PUMP	
					1 ~	3 ~				1 ~	3 ~	1 ~	3 ~	D2	
22SV01..D	1,1	80	399	263	263	-	-	399	137	129	155	155	120	15,5	26,9
22SV02..D	2,2	90	409	298	298	-	-	409	151	134	174	174	140	17,2	35,4
22SV03..D	3	100	467	-	298	-	-	467	-	134	-	174	160	19,4	40,4
22SV04..D	4	112	515	-	319	515	301	515	-	154	-	197	160	20,7	47,1
22SV05..D	5,5	132	630	-	375	630	349	630	-	168	-	214	300	26,7	65
22SV06..D	7,5	132	678	-	367	678	397	678	-	191	-	256	300	28	84
22SV07..D	7,5	132	726	-	367	726	445	726	-	191	-	256	300	29,3	86
22SV08..D	11	160	804	-	428	804	493	804	-	191	-	256	350	33,1	104
22SV09..D	11	160	852	-	428	852	541	852	-	191	-	256	350	34,4	105
22SV10..D	11	160	900	-	428	900	589	900	-	191	-	256	350	35,8	107
22SV12..D	15	160	996	-	494	996	685	-	-	240	-	313	350	38,4	141
22SV14..D	15	160	1092	-	494	1092	781	-	-	240	-	313	350	41,1	144
22SV17..D	18,5	160	1236	-	494	1236	925	-	-	240	-	313	350	45,1	156

22sv-2p50-en_d_td

22SV SERIES
OPERATING CHARACTERISTICS AT 50 Hz, 2 POLES


These performances are valid for liquids with density $\rho = 1.0$ Kg/dm³ and kinematic viscosity $\nu = 1$ mm²/sec.